

LED UFO SOLAR STREET LIGHT

BUILT IN MPPT
SOLAR CHARGING
CONTROLLER

PHOTOCELL
ACTIVATES LIGHT
AT DUSK

Using the latest Solar and LED technology our powerful LED UFO Solar light offers exceptional lighting with substantial energy savings, reduced maintenance costs and carbon emissions.

Once installed the lights charge up during the day and light up automatically at night for 7 hours.

25 YEAR
LIFE-SPAN
PEACE OF MIND
AND UNRIVALED
QUALITY

Easy fixing points to connect to your existing column make it easier than ever to update your current lighting, or if needed can be supplied with own column.

EASY FIX
CONNECT TO
EXISTING
COLUMNS OR
SUPPLIED WITH
OWN COLUMN

FEATURES

- Can be installed to areas with no electrical cabling
- Market leading efficiency
- Built in photocell activates light at dusk and stays on until dawn
- PIR sensor allows for timed use

REDUCES
YOUR ENERGY
CONSUMPTION

CAN BE
INSTALLED TO
AREAS WITH
NO ELECTRICAL
CABLING

APPLICATIONS

- Public spaces
- Security areas
- Exterior retail, commercial, hotel and leisure environments

**3
YEAR
GUARANTEE**



Technology Specification

**LED UFO SOLAR
STREET LIGHT**

MODEL VG-015W-UFO

SOLAR PANEL	RATED OUTPUT	18V/25W (Monocrystalline PV)
	LIFE-SPAN	25 years
BATTERIES	TYPE	LiFePO4 Battery 12.8V/9AH
	LIFE-SPAN	5~8 years
CONTROLLER	TYPE	MPPT / Waterproof class: IP68
	SENSOR	PIR (Timing as optional)
LED LIGHT SOURCE	RATED POWER	9V 15W
	LED BRAND	Bridgelux 1W + EPISTAR 2835
	LUMENS (LM)	1500-1800lm
	LIFE-SPAN	50000 hours
	VIEWING ANGLE	120°
FULL CHARGE TIME	BY SOLAR	5 hours (with enough solar power)
DISCHARGE TIME	FULL POWER	> 7 hours
	ENERGY SAVING	> 35 hours
WORKING TEMP.		-30°~+80°
COLOR TEMP.		Cool White 6000K (6000-6500k)/(Warm White 3000K, 4000K available)
MOUNTING HEIGHT		3~4 m
SPACE BETWEEN LIGHTS		12~15m
MATERIALS		Aluminium Alloy
CERTIFICATE		CE/ROHS/IP65
WARRANTY		3 years
PACKING & WEIGHT	PRODUCT SIZE	Diameter: 510mm, Height: 230mm, Pole Diameter:70~76mm
	NET WEIGHT	8.2kg
	CARTON TYPE	Customary Carton/ OEM Acceptable
	CARTON SIZE	570*570*280mm
	QTY/CTN	1pcs per carton
	GW. PER CARTON	10.0 kg
PCS PER CONTAINER	20' GP	330
	40' GP	680



Videre Global has used its best endeavours to ensure that the information contained in this publication is correct at the time of printing.

Unless otherwise agreed by us in writing, any contract to purchase products referred to in this brochure and any advice which we give in connection with the supply of products are subject to our standard conditions of sale. Videre Global reserves the right to change specifications, colours and features of the products and items illustrated and described in this publication at any time. Throughout this publication whenever a feature has been described as optional you should assume that it will be at extra cost to the base product. Some images may portray pre-production models and/or computer generated; therefore, the design/features of the final version may differ in various respects. In addition some of the features shown on the product may be optional. All products are subject to availability.

Please contact your local Videre Global representative if you have any questions.



www.videreglobe.com
sales@videreglobe.com